



Service with Energy.

# HOS STORMRIDGE

## 265W Offshore Supply Vessel



### DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	260 ft 0 in (79.2 m)	<b>Beam:</b>	60 ft 0 in (18.3 m)	<b>Draft Max:</b>	16 ft 9 in (5.11 m)
<b>Gross:</b>	2,520 GT	<b>Net :</b>	756 NT	<b>Draft Min:</b>	8 ft 6 in (2.59 m)
<b>IMO:</b>	9246877	<b>O.N.:</b>	1124421	<b>Flag:</b>	U.S.
<b>Certifications:</b>	Oceans-SOLAS, SIP, USCG Subchapter I, USCG Subchapter L				
<b>Classifications:</b>	+A1, +AMS, +DPS-2, American Bureau of Shipping, Loadline, OSV				

### PERFORMANCE

<b>Max Speed:</b>	12.0 kts	138 gal/hr (522 l/hr)
<b>Cruise Speed:</b>	10.0 kts	100 gal/hr (379 l/hr)

### PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	2 x Caterpillar 3608	<b>Total Horsepower:</b>	6,780 hp
<b>Propellers:</b>	CPP, High Efficiency, 4-Blade	<b>Propeller Diameter:</b>	118in (2,997mm)
<b>Shaft Generators:</b>	2 x Main Engine Driven	<b>Total Rating:</b>	4,000 kW
<b>Primary Generators:</b>	3 x Caterpillar 3406	<b>Total Rating:</b>	960 kW
<b>Bow Thruster:</b>	2 x Brunvoll CPP Tunnel	<b>Total Horsepower:</b>	2,400 hp
<b>Stern Thruster:</b>	2 x Brunvoll CPP Tunnel	<b>Total Horsepower:</b>	1,200 hp
<b>Rudder:</b>	Independent Steering, Schilling Fishtail	<b>Power Generation:</b>	480V/60 Hz/3-Phase

### CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	3,659 LT (3,718 MT)	<b>Deck Area:</b>	182ft x 48ft (8,736ft <sup>2</sup> )
<b>Deck Cargo:</b>	2,885 LT (2,931 MT)		55.5m x 14.6m (811.6m <sup>2</sup> )
<b>Dry Bulk:</b>	10,200 ft <sup>3</sup> (289 m <sup>3</sup> )	<b>Deck Load Rating:</b>	1,024 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )
<b>Brine:</b>	10,350 bbl (1,645 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Liquid Mud:</b>	10,350 bbl (1,645 m <sup>3</sup> )	<b>Discharge Rate:</b>	407 GPM (93 m <sup>3</sup> /hr)
<b>Potable Water:</b>	20,430 gal (77 m <sup>3</sup> )	<b>Discharge Rate:</b>	407 GPM (93 m <sup>3</sup> /hr)
<b>Rig Fuel:</b>	146,000 gal (553 m <sup>3</sup> )	<b>Discharge Rate:</b>	550 GPM (125 m <sup>3</sup> /hr)
<b>Rig Water:</b>	392,734 gal (1,486 m <sup>3</sup> )	<b>Discharge Rate:</b>	550 GPM (125 m <sup>3</sup> /hr)
<b>Cooler Area:</b>	850 ft <sup>3</sup> (24 m <sup>3</sup> )	<b>Freezer Area:</b>	850 ft <sup>3</sup> (24 m <sup>3</sup> )

### ELECTRONICS

Auto Pilot, Beier IVCS 2000, C-Nav, CCTV Cameras, Depth Sounder, DGPS, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/loudhailer, Radar (S-band), SARTs, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

### ACCOMMODATIONS

13 air conditioned/heated staterooms certified for 24 person berthing.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.